



# Plagiarism Checker X Originality Report

**Similarity Found: 18%**

Date: Saturday, April 29, 2023

Statistics: 589 words Plagiarized / 3290 Total words

Remarks: Low Plagiarism Detected - Your Document needs Optional Improvement.

---

## 63 PEDESTRIAN SPACE CAPACITY AND MOVEMENT PATTERN FOR ELEMENTARY STUDENTS IN URBAN AND RURAL AREA \*Febriane

Paulina Makalew<sup>1</sup>, Sakti Adji Adisasmita<sup>2</sup>, Shirly Wunas<sup>3</sup> and Sumarni Hamid Aly<sup>4</sup> <sup>1</sup>Postgraduate School, Hasanuddin University, Indonesia; <sup>1</sup>Civil Engineering Department, Polytechnic Manado, Indonesia, <sup>2,4</sup>Civil Engineering Department, Hasanuddin University, Indonesia; <sup>3</sup>Architecture Department, Hasanuddin University, Indonesia \* , Received: 4 March 2018, Revised: 5 April 2018, Accepted: 18 April 2018 ABSTRACT: Elementary students as children pedestrians on their journeys to school, demonstrate the way they use space and movement pattern.

Their unique space used can be seen on the pedestrian pathway in which safety should be the priority. Study space capacity of children pedestrian pathway and their movement pattern is urgent since there is limited research in related to child pedestrians and there is an inadequate guideline for it in the urban and rural area. The aim of this research is to analyze children space capacity and movement pattern.

Data is taken in the form of video recording and photos using camera and smartphone and is counted using drawing program AutoCAD 2016 for measurement. Research location is 14 elementary schools in the urban area of the city of Manado and 9 schools in the rural area of Minahasa, North Minahasa, and Sangihe Island. The sample is based on Krejcie Morgan formula where there is a need for a minimum of 383 children considering the number of the population of elementary students in North Sulawesi province, Indonesia. Data is analyzed using SPSS 24.

Results are children pedestrian space capacity with consideration to the number of children in a walking group and straight and zig-zag movement pattern. There is a

need to have a special child pedestrian standard for the urban and rural area. Future research could develop the variant of location and time in which children walk to their destination, such as shopping precinct and housing area.

Keywords: Children pedestrian, an elementary student, space capacity, movement pattern, North Sulawesi

## 1. INTRODUCTION

Walking is a transportation mode for the journey to a destination [1]. As one of the active transportation s, walking is a process or activity of moving people or goods from one place to another [2].

Children need safe and adequate space for their activity. Mobility helps children to interact with the environment [3]. However, pedestrian pathways in Manado are not safe, not well maintained and most of the streets do not have pedestrian pathways [4], [5], [6]. In terms of the street problem in Manado, there is congestion caused by all types of vehicles and movement of goods and people in Manado [7].

Moreover, transport problem of pollution and traffic jam should consider car emissions [8] and manage an efficient public transport such as campus bus [9]. School as a destination for the students requires a good access and its facility along the street. According to neighborhood standards, a school requires pedestrian pathways for a radius of 1000 meters for elementary school.

By walking to school, children can have a detailed knowledge regarding the local environment, the texture of landscape by exploring along their journey. The pedestrian pathway should be safe and comfortable for children as part of a planning principle for a pathway system in suburban areas [10]. Special guidelines for child pedestrians have not been formed yet.

Therefore, there is a need to study child space movement and capacity along streets in urban and rural areas.

## 2. LITERATURE REVIEW

### 2.1 Pedestrian Pathway

Pedestrian pathway for children is an area that children use for their journey to and from school. An area for a pedestrian in this research is an area including pedestrian pathways, side roads and any open space in the primary, secondary and local streets.

### 2.1 Pedestrian Space Capacity

Pedestrian space capacity is related to space movement on the pathway and different factors influence it. One factor that influences capacity is speed [11], [12], [13]. The characteristics of pedestrian flow for students aged 18 to 25 years [14]. For pedestrian behavior [11], this research study the capacity for three groups of age less than 20 years, 20 to 65 years and more than 65 years old.

Pedestrian volume studies in research are analyzed for facility needs and pedestrian

behavior [15]. 2.1 Pedestrian Movement Pattern International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp. 63 - 69 ISSN: 2186-2982 (P), 2186-2990 (O), Japan, DOI: <https://doi.org/10.21660/2018.50.52440> Special Issue on Science, Engineering & Environment International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp.

63 - 69 64 The movement pattern is a movement of an elementary student on the pathway along their journey to and from school. The trip pattern has been used as an important factor in research for school children [16] in related to counting the calorie usage for walking. Route choice shapes movement pattern according to behavior analysis [15], route choice based on pedestrian choice [3], [16] and as part of behavior model evaluation [16]. 3. METHODS Research sample population is elementary students grade 1 to 6 with age between 6 to 12 years old.

Research location is North Sulawesi Province in Indonesia with a total potential number of students 281,853 consists of 183,167 students in the rural area and 98,363 students in an urban area [17]. Using the Krejcie Morgan formula for limited population [18] such as a number of students there is a need for 383 sample for each area.

Data were taken from a sample of pedestrian elementary students from 23 schools in the urban and rural area. The sample distribution can be seen in the figure below. Fig. 1 North Sulawesi elementary students sample distribution map Data is taken by camera and smartphone when students are walking to and from school and their activities in school hours on the pedestrian pathway. Recording and photos are taken undisclosed, unknown by students to get natural data.

Data for dimension and movement pattern is measured and drawn using computer program AutoCAD 2016 and Ms. Office Excel for total calculation. All data is analyzed using computer program SPSS 24 to get a description related to the result of mean, mode, maximum and minimum dimension. 4. RESULT AND DISCUSSION 4.1 Child Pedestrians Dimension and Space Capacity The result of child pedestrian s' width can be seen in the figure below.

From the sample available in the urban and rural area, 387 sample in each area is measured and counted using SPSS 24 statistic program. Table 1 Comparison of child pedestrian width and standard Type of Value Urban (m) Rural (m) Standard (m) Source Adult (A)/ Child (C) Mean 0.78 0.81 1.2 [19] A 1.6 [21] A 0.8 [20] A 1 [21] A 1.5

[21] A & 1 C MANADO State Elementary School (SES)15, 18 & 20 (68 Students (St)), ES GMIM 06 BAHU (15 St), ES GMIM 35 BAHU (44 St), Catholic ES DON BOSCO PANIKI (18 St), Catholic ES XVII Tarsisius Winangun (52 St), SES 3 Singkil (40 St), SES 29 Singkil (96

St), SES 88 Singkil (59 St), Inpres ES Kaiwatu Politeknik (28 St), SES Winangun (18 St) SANGIHE ISLAND Inpres ES Laine South Manganitu (22 St), Gmist ES Laine Kec.

South Manganitu (39 St) NORTH MINAHASA Inpres ES 1 & 2 Talawaan (44 St), ES GMIM 63 Paslaten Likupang (57 St) MINAHASA Inpres ES Tambala (69 St), Advent ES Tanawangko (52 St), Gmim ES 150 Tanawangko (55 St), Gmim ES Upper Winangun (44 St) International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp. 63 - 69 65 This research found that the average dimension of width pathway in urban areas is smaller than in rural area. The average width of the urban area is 0.78 m and in a rural area is 0.81 m. maximum width in an urban area is 1.65 m and in a rural area is 1.78 m.

With a group of walking students in a rural area up to 14 students and in the urban area up to 7 students, average group of walking in the rural area is larger than an urban area, an average walking group in the rural area is 3 students while in an urban area is 2 students. Child pedestri width per person is less than standard available which indicate that space is adequate.

However, considering the number children in a group of walking in the rural area is larger than urban area than the size should be different. The number of a walking group and the frequency per act is dominated by two and three students. By comparison, a student is more likely to walk alone. The comparison can be seen in the next figure. Fig. 2. Comparison of frequency of student pedestrians per act and number of walking group (a) (b) Fig.

3 Children pedestrian width in (a) urban area and (b) rural area Based on the width of children pedestrian in the rural and urban area, section street consists children pedestrian area can be planned. The example is for the local street with the 6-meter-wide premier street in the urban and rural area as shown in figures 4 and 5. 0 50 100 150 200 250 300 350 400 450 500 550 1 2 3 4 5 6 7 8 9 10 11 12 13 14 Frequency of students pedestrian per act Number of children in a walking group NUMBER OF ELEMENTARY STUDENTS PEDESTRIAN URBAN RURAL International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp. 63 - 69 66 Fig.4

Street section with children pedestrian area for 6-meter-wide premier urban street Fig.5 Street section with children pedestrian area for 6-meter-wide premier rural street Considering the numbers of the walking group, the width of the pedestrian pathway for children is counting and the result of average width child pedestrians is 1.566 m with average 2 students for urban area and 2.343 m for rural area with average 3 students. Based on this result the size is larger than a standard such as by Highway Capacity Manual [20] with 0.8

m standard for adult and by Ministry of Public Works [21] with 1 m standard for an adult carry bag. Space capacity of elementary student pedestrians, based on movement, can be seen in table 2. Table 2 Comparison result of space capacity with standard and previous research

Type of Value	Urban (m <sup>2</sup> )	Rural (m <sup>2</sup> )	Previous Research /Standard (m <sup>2</sup> )
Source A / C Mean	0.783	0.842	0.4 0.9 [11]
A	1.35	1.62	[21]

Note. A=Adult, C=Child Space capacity of elementary students in this research is larger than previous research.

Average space capacity is 0.783 m<sup>2</sup> in urban area and 0.842 m<sup>2</sup> in rural area. By comparison, average space capacity [11] is between 0.4 to 0.9 m<sup>2</sup>. Considering the number of walking group in the urban and rural area is different as discussed before, space capacity in an urban area for average 2 students is 1.566m<sup>2</sup> and in a rural area with 3 students is 2.526 m<sup>2</sup>. Space capacity in a rural area is larger than Ministry of Public works standard with average 1.35 to 1.62 m<sup>2</sup> for adult walking and carrying goods. 4.2

Children Pedestrian Movement Pattern Elementary students ' pedestrian movement pattern in the urban and rural area found in this research is dominated by straight pattern and followed by a zig-zag pattern [22]. The curve below shows a comparison of the frequency of movement and group of elementary students with the straight pattern.

Although the percentage of zig-zag movement is less than straight movement, the space usage is significantly larger. The percentage of movement pattern can be seen in table 3. Table 3 Number of movement pattern

Type of Movement	Urban	Rural	Amount	% Amount
Straight	722	98.63	468	93.79
Zig-zag	3	0.41	26	5.21
Half zig- zag	0	0	1	0.20
Zig-zag & straight	7	0.96	4	0.80
Total	732	499		

International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp.

63 - 69 67 Zig-zag movement using maximum area of the street wherein the local street is 3-meter-wide and for the secondary and premier street is 6- meter-wide which shown in figure 6 and 7. Fig. 6 Space usage based on movement pattern zig-zag and straight movement in the rural area Fig. 7 Space usage based on movement pattern zig-zag and straight movement in an urban area This research considers aspects as in previous research such as school neighborhood character [23], destination of child journey [24], access to outdoor landscape [3], obstacles in the environment [25] and child pedestrian behavior [26].

Considering all these aspects, movement pattern is analyzed and the pattern found is straight and zig zag. From this result of pedestrian space capacity and movement

pattern, it is important to give priority to children as pedestrians. In the intersection area where there is no crossing area, children use the **area of the street** which is dominated by vehicles (Fig.8). Fig.

8 Zig zag movement pattern on intersection area without crossing area By giving priority to child pedestrians, area potential for a zig-zag movement pattern such as in street intersection can have priority areas such as a special area for crossing and a zig-zag movement which can be seen on figure 9. Fig. 9 Crossing area for zig-zag movement on the intersection of the street 5.

CONCLUSION Elementary student pedestrian space capacity show differences **in the urban and rural area** in terms of dimension and space area. By comparison with previous research and standards available, the result show adequate dimension and size per person yet need to consider the number of walking group **International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp.**

63 - 69 68 Result dimension width of children pedestrian for rural area is larger than an urban area. The group walking children **in the rural area** is larger up to 14 students while **in an urban area** is up to 7 children. In terms of the pedestrian movement pattern, **in the urban and rural area**, it has found a straight and zig-zag pattern.

Although the proportion of zig-zag pattern is less than the straight patterns, the space usage influence significantly due to maximum use of space available on street. In 3-meter-wide local street as well as 6-meter-wide secondary and primer street in both areas, space usage is as wide as these sizes. Although aspects considered in this research for movement pattern using previous research, movement pattern found such as a zig-zag is a unique one.

The number of children in the walking group influence the width **of children pedestrian pathway** is another new finding. Therefore, it will need to establish a rule for children pedestrian particularly in an area dominated by children. In the future, a variant of location such as a public area, shopping precinct, and neighborhood of housing and settlement could be explored. 6.

REFERENCES [1] Adisasmita, Sakti Adji, Comprehensive Transportation and Multi-Mode - Transportasi Komprehensif dan Multi Moda, Graha Ilmu, Yogyakarta 2014 [2] Morlok, E, K., Introduction to Transportation Engineering and Planning, McGraw-Hill, New York 1985 [3] Björklid, Pia, and Maria Nordström, "Eontl hild -Friendliness: Coboatn nd urResearh.

Children, Youth, and Environments 17(4) 2007 pp 388- 401 [4] Makalew, Febriane Paulina, Toward Great Streets Using Urban Design Approach, The Case Study of Manado, The International Conference on Environmentally Friendly Civil Engineering Construction and Materials Proceeding Book, Manado, Indonesia, 13 – 14 November 2014, ISBN: 978-602-71876-0-3 [5] Makalew, Febriane Paulina, Identification of Urban Street Facility: Challenge for Walking as Environmental Friendly Transportation - Identifikasi Fasilitas Jalan Perkotaan: Tantangan Jalan Kaki Sebagai Transportasi Ramah Lingkungan, Studi Kasus Kota Manado, Proceeding Research Unit Manado State Polytechnic 2014 [6] Makalew, Febriane Paulina., Adisasmita, Sakti Adji.,

Was, Shirly dan Hamid, Sumarni, Space Requirement for Tree and Pedestrian Space Movement, Proceeding The 2nd Asia Pacific Environment and Landscape Architecture Forum (APELA) 2016, Seoul National University, South Korea [7] Widodo, Bambang Patmo., Sulistio, Harnen., Wicaksono, Achmad and Djakfar, Ludfi., Analysis of Traffic Characteristics and Goods Transport in Manado, Indonesia, International Journal of GEOMATE, Dec., 2017, Vol. 13, Issue 40, pp.112-117 [8] Aly, S.H. & Ramli, M.I.. A Development of MARNI 12.2 Model: A Calculation Tool of Vehicular Emission For Heterogeneous Traffic Conditions 11. 43-50 10.3923/jeasci. 2016. 43.50 [9] Putera, Riza., Santoso, Anisa., Sondang, Irene., Pratama, Oky., Nandhito, Garrin and Suyanti, Esty.,

Efficiency of Public Transportation Using Global Navigation Satellite System (GNSS) International Journal of GEOMATE, Aug, 2017, Vol.13, Issue 36, pp 26-30 [10] Wunas, Shirly, Kota Humanis, Intergrasi Guna Lahan dan Transportasi di Wilayah Suburban, Berlian Internasional, Surabaya 2011 [11] Daamen, W, & Hoogendoorn, S P, Experimental Research Of Pedestrian Walking Behaviour, Transportation Research Record 1828, 2003 pp 20-30 [12] Nazir, M. I., Al Razi, K. M.

A., Hossain, Q. S. and Adhikary, S. K., Pedestrian Flow Characteristics at Walkways in Rajshahi Metropolitan City of Bangladesh, Proceedings of the 2nd International Conference on Civil Engineering for Sustainable Development, (ICCESD-2014), KUET, Khulna, Bangladesh [13] Papadimitriou, Eleonora.,

George Yannis and John Golias, A Critical Assessment Of Pedestrian Behaviour Models, Trans. Res. Part F 12 (2009) pp 242 – 255 [14] Navin, F.P.D. and R. J. Wheeler, Pedestrian Flow Characteristics, Traffic Engineering 39, 1969 pp 30-36, [15] Juniardi, Analysis of Crossing Facility Need and Pedestrian Crossing Behavior on Kartini Street Bandar Lampung - Analisis Kebutuhan Fasilitas Penyeberangan Dan Perilaku Pejalan Kaki Menyeberang Di Ruas Jalan Kartini Bandar Lampung, Jurnal Teknik Sipil UBL Volume 1 No. 1, Oktober 2010 [16] Mackett, Roger L.

and James Paskins, Children's PicaActy: Tntibutn of Playing and Walking, Centre for Transport Studies, Children & Society Volume 22, (2008) pp 345 – 357 [17] Biro Pusat Statistik (BPS) Statistic of North Sulawesi Province, Social North Sulawesi in figures (BPS-Statistics of North Sulawesi Province) chapter 4 2016 pp 81 142 International Journal of GEOMATE, Oct., 2018 Vol.15, Issue 50, pp. 63 - 69 [18] Krejcie, Robert V. and Morgan, Daryle W.,

Determining Sample Size for Research Activities, Educational and Psychological Measurement 30, 1970 pp. 607-610 [19] Indonesia National Standard Board (INSB) Badan Standarisasi Nasional Indonesia, 2004, SNI 03-1733-2004 Guideline for Housing Planning in Urban Area, Tata Cara Perencanaan Lingkungan Perumahan Di Perkotaan [20] Transportation Research Board (TRB), Highway Capacity Manual (HCM), National Research Council Washington DC 2000 [21] Kementerian Pekerjaan Umum - Ministry of Public Works, Guidance for Planning, Provider and Use of Pedestrian Pathway facilities in Urban Area - Pedoman Perencanaan, Penyediaan, Dan Pemanfaatan Prasarana Dan Sarana Jaringan Pejalan Kaki di Kawasan Perkotaan, Peraturan Menteri Pekerjaan Umum Ministry of Public Works Regulation No: 03/PRT/M/2014 [22] Makalew, Febriane Paulina., Adisasmita, Sakti Adji.,

Wunas, Shirly and Hamid, Sumarni, Children Pedestrian Movement Pattern on Pedestrian Pathway - Pola Pergerakan Pejalan Kaki Anak pada Jalur Pedestrian, National Seminar in Civil Engineering (SeNaTS) 2 Proceeding Book, Udayana University, Denpasar Bali 2017 [23] Curtis, Carey., Babb, Courtney and Olaru, Doina, Built Environment And Children's Travel To School, Transport Policy Volume 42, August 2015, pp 21 – 33 [24] Westman, Jessica, Maria Johansson, Lars E.

Olsson, Fredrika Mårtensson, Margareta Frn,Cen' Afive xpernce of Every-Day Travel, Journal of Transport Geography 29 (2013) pp 95 – 102 [25] Napier, Melissa A., Brown, Barbara B, Werner, Carol M., Gallimore, Jonathan, Walking To School: Community Design And Child And Parent Barriers, Journal of Environmental Psychology Volume 31, Issue 1, March 2011, pp 45 51 [26] Makalew, F P., Adisasmita S A., Wunas S., Hamid S, Influence of Children Pedestrian Behaviour on Pedestrian Space Usage, IOP Conf. Ser.: Mater. Sci. Eng.

2017, 271 012028 Copyright © Int. J. of GEOMATE. All rights reserved, including the making of copies unless permission is obtained from the copyright proprietors.

INTERNET SOURCES:

-----  
3% -



[https://www.researchgate.net/profile/Febriane-Makalew/publication/326097714\\_Pedestrian\\_space\\_capacity\\_and\\_movement\\_pattern\\_for\\_elementary\\_students\\_in\\_urban\\_and\\_rural\\_area/links/5e55accfa6fdccbeba0303e8/Pedestrian-space-capacity-and-movement-pattern-for-elementary-students-in-urban-and-rural-area.pdf](https://www.researchgate.net/profile/Febriane-Makalew/publication/326097714_Pedestrian_space_capacity_and_movement_pattern_for_elementary_students_in_urban_and_rural_area/links/5e55accfa6fdccbeba0303e8/Pedestrian-space-capacity-and-movement-pattern-for-elementary-students-in-urban-and-rural-area.pdf)

1% - <https://onsearch.id/Record/IOS5734.1871/TOC>

1% - <http://repository.polimdo.ac.id/1871/>

1% -

[https://www.researchgate.net/publication/336789049\\_Child\\_Pedestrian\\_Friendly\\_Design\\_Principle\\_for\\_the\\_Settlement\\_and\\_Housing\\_area](https://www.researchgate.net/publication/336789049_Child_Pedestrian_Friendly_Design_Principle_for_the_Settlement_and_Housing_area)

1% -

[https://www.researchgate.net/publication/316942884\\_Efficiency\\_of\\_public\\_transportation\\_using\\_global\\_navigation\\_satellite\\_system\\_GNSS](https://www.researchgate.net/publication/316942884_Efficiency_of_public_transportation_using_global_navigation_satellite_system_GNSS)

<1% - <https://www.atlantispress.com/article/125965023.pdf>

1% - <https://geomatejournal.com/geomate/article/download/951/813/1056>

1% -

[https://www.researchgate.net/publication/227629748\\_Children's\\_Physical\\_Activity\\_The\\_Contribution\\_of\\_Playing\\_and\\_Walking](https://www.researchgate.net/publication/227629748_Children's_Physical_Activity_The_Contribution_of_Playing_and_Walking)

1% -

[https://www.researchgate.net/publication/338371357\\_Motivational\\_Factors\\_to\\_Learn\\_English\\_among\\_University\\_Students\\_in\\_An\\_Urban\\_Area](https://www.researchgate.net/publication/338371357_Motivational_Factors_to_Learn_English_among_University_Students_in_An_Urban_Area)

4% -

[https://www.researchgate.net/publication/326097714\\_Pedestrian\\_space\\_capacity\\_and\\_movement\\_pattern\\_for\\_elementary\\_students\\_in\\_urban\\_and\\_rural\\_area](https://www.researchgate.net/publication/326097714_Pedestrian_space_capacity_and_movement_pattern_for_elementary_students_in_urban_and_rural_area)

<1% -

<https://stackoverflow.com/questions/65142286/calculating-average-width-of-polygons>

<1% - <https://www.pu.go.id/assets/images/pdf/announce20160715100516.pdf>

1% -

[https://www.researchgate.net/publication/321661805\\_Influence\\_of\\_children\\_pedestrian\\_behaviour\\_on\\_pedestrian\\_space\\_usage](https://www.researchgate.net/publication/321661805_Influence_of_children_pedestrian_behaviour_on_pedestrian_space_usage)

1% - <https://geomatejournal.com/geomate/article/download/973/832/1080>

<1% - <https://geomatejournal.com/geomate/article/download/1377/1316/1731>

<1% -

[https://www.researchgate.net/publication/366722700\\_Ketersediaan\\_Infrastruktur\\_Kawasan\\_Perumahan\\_Sederhana\\_Studi\\_Kasus\\_Perumahan\\_Politeknik\\_Indah](https://www.researchgate.net/publication/366722700_Ketersediaan_Infrastruktur_Kawasan_Perumahan_Sederhana_Studi_Kasus_Perumahan_Politeknik_Indah)

<1% -

[https://www.researchgate.net/publication/321759346\\_Pedestrian\\_Flow\\_Characteristics\\_at\\_Walkways\\_in\\_Rajshahi\\_Metropolitan\\_City\\_of\\_Bangladesh](https://www.researchgate.net/publication/321759346_Pedestrian_Flow_Characteristics_at_Walkways_in_Rajshahi_Metropolitan_City_of_Bangladesh)

1% - <https://www.linkedin.com/in/nishanbiswas>

<1% - <https://scholar.google.com/citations?user=ogwo2IQAAAAJ>

<1% - <http://jurnal.ubl.ac.id/index.php/JTS/article/view/252/256>

<1% - <http://jurnal.ubl.ac.id/index.php/JTS/article/download/251/255>

<1% - [https://www.ucl.ac.uk/~ucetjop/pdf/chso\\_113.pdf](https://www.ucl.ac.uk/~ucetjop/pdf/chso_113.pdf)

<1% -

<https://www.developmentaid.org/donors/view/198717/directorate-general-of-cipta-karya-a-ministry-of-public-works-and-public-housing-direktorat-jendral-ci>

<1% -

<https://sumbarprov.go.id/home/news/7205-pedoman-perencanaan-penyediaan-dan-pe-manfaatan-prasarana-dan-sarana-jaringan-pejalan-kaki-di-kawasan.html>

<1% - <https://abdiinsani.unram.ac.id/index.php/jurnal/article/view/737>

<1% -

[https://www.researchgate.net/publication/339129521\\_Influence\\_of\\_elementary\\_students\\_walking\\_speed\\_to\\_children\\_pedestrian\\_pathway\\_planning](https://www.researchgate.net/publication/339129521_Influence_of_elementary_students_walking_speed_to_children_pedestrian_pathway_planning)

1% - <https://conservancy.umn.edu/handle/11299/181562>